



## Data Sheet 1427354


**Product:** S16/1 VP br. imp.r.lys PH  
**El-number:** 1427354  
**Mat.no:** EKO04311  
**EAN:** 7020160431110  
**Packing:** 5  
**Color:** Polarwhite




**Product description:** IP55 surface mounted switch with pilot lamp in rocker. The switch-house is made of thermosetting plastic, except the rocker of thermoplastic. Classification: IP 55. Connecting piece L 469 makes it possible to connect and combine two or more switches or socket-outlets. One extra fixed earth-terminal inside the bottom of the housing. Knock-out holes in the corner for the condensation-water is at disposal.

**Technical specifications:** 1 pole - push button with pilot lamp.  
Surface mounted  
Color: Polarwhite.  
16A / 250 V.  
Degree of protection: IP55.  
Temperature: -30 - +35.  
Halogenfree.  
Standard IEC 669-1.  
Conduit connection length: 8mm  
Amount of conduits pr terminal: 2  
Maximum torque: 0,8Nm (According to IEC 62196-1)  
Maximum cross section: 4mm<sup>2</sup>

Size



Wiring diagram



### ELKO AS

E-mail: elko@elko.no  
Internet: www.elko.no  
Bank: 6219.05.15880  
Org.no.: NO 911 382 563 MVA

ELKO Front office  
Sandstuveien 68, NO-0680 Oslo  
P.O.Box 6598 Etterstad, NO-0607 Oslo  
Tel.: +47 67 80 73 00  
Fax: +47 67 80 73 01

ELKO Plant  
Sporvind Industriområde, NO-3340 Åmot  
Tel.: +47 32 78 91 00  
Fax: +47 32 78 91 01