

Applicant	ELKO AS Sandstuveien 68 0680 Oslo Norway
Manufacturer	ELKO AS Sandstuveien 68 0680 Oslo Norway
Factory	See next pages
Project Number	PRJ0011736
Product	Socket-outlet
Model/Type Ref.	L801 (D 1091 PT)
Ratings	16A 250V ~
Brandname / Trademark	ELKO
Principal Characteristics	Catalogue ID: D 1091 PT. Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw/screwless terminals. 60mm fixing distance. IP21 with RS and Plus design
A sample of the product was tested and found to be in conformity with	IEC 60884-1:2002, IEC 60884-1:2002/AMD1:2006, IEC 60884-1:2002/AMD2:2013 NEK 502:2016/AMD1:2022
Validity	<i>This certificate documents conformity with the standards shown, and also applies as license for use of Nemko's name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation.</i> <i>New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.</i>
Additional Information	
Additional model(s)	See next pages



Product	Socket-outlet
Variant	1
Model/Type Ref.	L800 (RS 1091 PT)
Ratings.	16A 250V ~
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS and Plus design
Product	Socket-outlet
Variant	2
Model/Type Ref.	L800 (RS 1091 LAV PT)
Ratings.	16A 250V ~
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS and Plus design
Product	Socket-outlet
Variant	3
Model/Type Ref.	L800 (1090 UPT IF)
Ratings.	16A 250V ~
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic / Thermosetting, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP44 with splashscreen type L478. For use in cold environment down to -25 °C.
Product	Socket-outlet
Variant	4
Model/Type Ref.	L800 (RS 1091 PT prosjektstikk)
Ratings.	16A 250V ~
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS and Plus design

Signature



Sweet Yuan

Certification department

Date of Issue

2023-08-11

Working for a more sustainable future
Please do not print



www.nemko.com

Product	Socket-outlet
Variant	5
Model/Type Ref.	L800 (H 1091 PT prosjektstikk)
Ratings.	16A 250V ~
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screwless terminals. 60mm fixing distance. IP21 with RS and Plus design
Product	Socket-outlet
Variant	6
Model/Type Ref.	L800 (Plus dbl rehabstikk m j)
Ratings.	16A 250V ~
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP 21 with plus design
Product	Socket-outlet
Variant	7
Model/Type Ref.	L801 (Plus 2-vägs snabb m j)
Ratings.	16A 250V ~
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Catalogue ID: Plus 2-vägs snabb m j. Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw/screwless terminals. 60mm fixing distance. IP21 with Plus design
Product	Socket-outlet
Variant	8
Model/Type Ref.	L3362 (RS 1091 PT DELT 440)
Ratings.	16A 250/440V ~
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Catalogue ID: RS 1091 PT DELT 440. Socket-outlet for fixed installation. With split output for separate phases. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. IP21 with RS and Plus design

Signature



Sweet Yuan

Certification department

Date of Issue

2023-08-11

*Working for a more sustainable future
Please do not print*



www.nemko.com

Product	Socket-outlet
Variant	9
Model/Type Ref.	L801 (DR 1091 PT)
Ratings.	16A 250V ~
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Socket-outlet for fixed installation. Alternative design. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with shutters and screw/screwless terminals. 60mm fixing distance. IP21 with RS and Plus design
Product	Socket-outlet
Variant	10
Model/Type Ref.	L800 (RS 1091)
Ratings.	16A 250V ~
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic, flush mounting, 2 gang, with screw terminals. 60mm fixing distance. IP21 with RS and Plus design
Product	Socket-outlet
Variant	11
Model/Type Ref.	L3362 (1090 UPT IF DELT 440)
Ratings.	16A 250V/440V ~
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Socket-outlet for fixed installation. Standard Sheet III. Thermoplastic / Thermosetting, flush mounting, 2 gang, with shutters and screw terminals. 60mm fixing distance. For use in cold environment down to -25°C. IP44 with splashscreen type L478

Factories
Merten GmbH
Fritz-Kotz-Strasse 8
DE-51674 Wiehl
Germany

AS M ja P Nurst
Ümarmäe tn 3 Kärdda
Hiiumaa 92414
Estonia

Signature



Sweet Yuan
Certification department

Date of Issue

2023-08-11

*Working for a more sustainable future
Please do not print*



www.nemko.com