



Data Sheet 4541110

Product: ELKO Wireless Quick dim
El-number: 4541110
Mat.no: EKO04992
EAN: 7020160499219
Packing: 1
Color: Polarwhite



Product description: Wireless kit for control of one LED* lightzone. The kit includes one WL dimmer el.no: 45 411 21 and one switch with four buttons el.no: 45 411 30. The dimmer can be hidden in the installation, and the switch is flat on the backside and can be mounted everywhere. Delivered in ELKO Plus design.


* For LED see www.elko.no for updated dimmertable and approved LED lightsources.

Technical specifications: Radiofrequency: 868MHz, GFSK-modulation, data rate 2,4 kbps.
Range: 300 m outdoors, 10-50 m indoors.

SWITCH :
Battery type: CR2032 (included).
Battery lifetime: 5-10 years or 40 000 operations.
Degree of protection: IP20.

DIMMER :
Load: 20-250VA LED, lightbulbs, electronic trafos or iron trafos.
Electronic thermic fuse and shortcircuit fuse with auto reset.
Thermofuse: 115°C without reset.
The dimmers demands connection of both L and N

Size



Wiring diagram

ELKO AS

E-mail: elko@elko.no
Internet: www.elko.no
Bank: 6219.05.15880
Org.no.: NO 911 382 563 MVA

ELKO Front office
Sandstuveien 68, NO-0680 Oslo
P.O.Box 6598 Etterstad, NO-0607 Oslo
Tel.: +47 67 80 73 00
Fax: +47 67 80 73 01

ELKO Plant
Sporpind Industriområde, NO-3340 Åmot
Tel.: +47 32 78 91 00
Fax: +47 32 78 91 01