Data Sheet 1478165

Product:	BF 120 Bevegelsesdetektor IP55
El-number:	1478165
Mat.no:	EKO05212
EAN:	7020160521217
Packing:	1
Color:	White

Product description:

The movement detector is intended for ceiling or wallmounting indoors and outdoors.
Select the installation site such that interference due to environmental influences are avoided.
The movement detector is a Passive Infra Red detector, reacting to moving heat from the human body. The movement detector stays active as long as the warm object is in its area of perception.
To ensure optimum detection, install the movement detector laterally to the direction of movement.
Supplied with special bracket for cornermounting.
Detection area is 120º , 12 meter distance if the detector is mounted at 2,5meters.

Technical specifications:

Voltage: 230V 50Hz
Max Load:
-LED:100W
-Ohmic load: 0-1000W
-230V halogen: 0-900W
-Electronic transformator: 250VA
-Flourescent lights with HF reactor: 200VA
Max fuse: 10A.
Detection distance: 12meters if mounting height is 2,5m
Detection area: 120º
Degree of protection: IP55
Timeajustement: 3sek - 30min
Brightness treshold: 5 - 2000 lux
Operational temperature: -15 - +40ºC
Color: Grey

ELKO AS

E-mail: elko@elko.no
Internet: www.elko.no
Bank: 6219.05.15880
Org.no.: NO 911 382 563 MVA

ELKO Front office
Sandstuveien 68, NO-0680 Oslo
P.O.Box 6598 Etterstad, NO-0607 Oslo
Tel.: +47 67 80 73 00
Fax: +47 67 80 73 01

ELKO Plant
Sporpind Industriområde, NO-3340 Åmot

Tel.: +47 32 78 91 00
Fax: +47 32 78 91 01

Size

Wiring diagram



ELKO AS

E-mail: elko@elko.no
Internet: www.elko.no
Bank: 6219.05.15880
Org.no.: NO 911 382 563 MVA

ELKO Front office
Sandstuveien 68, NO-0680 Oslo
P.O.Box 6598 Etterstad, NO-0607 Oslo
Tel.: +47 67 80 73 00
Fax: +47 67 80 73 01

ELKO Plant
Sporpind Industriområde, NO-3340 Åmot

Tel.: +47 32 78 91 00
Fax: +47 32 78 91 01