CERTIFICATE

P26229023/A1

Applicant	Schneider Electric Industries SAS 1884 Boulevard de la Défense 92500 Nanterre France
Manufacturer	Schneider Electric Industries SAS 1884 Boulevard de la Défense 92500 Nanterre France
Factory	Polplast Polska Sp. z o.o. ul. Burmistrza Andrzeja Marka 8 Myslenice, Malopolska 32 400 Poland
Project Number	PRJ0106213
Product	Concrete and hollow wall boxes
Model/Type Ref.	RED1M-9
Ratings	-
Brandname / Trademark	ELKO
Principal Characteristics	Single box low model 9mm of insulated material supplied with screws. Flush, semi-flush or embedded in hollow walls, hollow ceilings, hollow floors or furniture. Suitable for installation into concrete during the casting process. With inlets for other types of conductors/cables or conduits. With rigid/flexible spouts (hub), with cable retention. With clamping means for flexible conduit. Alternative design with fire protecting pad. Minimum and maximum temperature during installation -25°C to +60°C. Maximum temperature during the casting process +90°C. Class Ha. IP30
Replaces	This certificate replaced previous certificate No. P26229023, due to changed in address of applicant and manufacturer.
A sample of the product was tested and found to be in conformity with	Safety EN IEC 60670-1:2021;A11
Validity	*This certificate documents conformity with the standards shown, and also applies as license for use of Nemko's name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation.* *New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.*
Additional Information	
Additional model(s)	See next pages

Signature

Jiyea Gim

Jiyea Gim

Certification department

Date of Issue

2026-08-24

Working for a more sustainable future
Please do not print

Nemko Group AS
Philip Pedersens vei 11
1366 Lysaker, Norway
TEL +47 22 96 03 30
info@nemko.com
ENTERPRISE NUMBER
NO974404532

www.nemko.com

CERTIFICATE

P26229023/A1

Product	Concrete and hollow wall boxes
Variant	1
Model/Type Ref.	RED1M-26
Ratings.	-
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Single box low model 26mm of insulated material supplied with screws. Flush, semi-flush or embedded in hollow walls, hollow ceilings, hollow floors or furniture. Suitable for installation into concrete during the casting process. With inlets for other types of conductors/cables or conduits. With rigid/flexible spouts (hub), with cable retention. With clamping means for flexible conduit. Alternative design with fire protecting pad. Minimum and maximum temperature during installation -25°C to +60°C. Maximum temperature during the casting process +90°C. Class Ha. IP30

Product	Concrete and hollow wall boxes
Variant	2
Model/Type Ref.	RED15M-13
Ratings.	-
Brandname / Trademark (if different from page 1)	
Principal Characteristics	1.5M box low model 13mm of insulated material supplied with screws. Flush, semi-flush or embedded in hollow walls, hollow ceilings, hollow floors or furniture. Suitable for installation into concrete during the casting process. With inlets for other types of conductors/cables or conduits. With rigid/flexible spouts (hub), with cable retention. With clamping means for flexible conduit. Alternative design with fire protecting pad. Minimum and maximum temperature during installation -25°C to +60°C. Maximum temperature during the casting process +90°C. Class Ha. IP30

Product	Concrete and hollow wall boxes
Variant	3
Model/Type Ref.	RED2M-13
Ratings.	-
Brandname / Trademark (if different from page 1)	
Principal Characteristics	Two-folded box of low model 13mm of insulated material supplied with screws. Flush, semi-flush or embedded in hollow walls, hollow ceilings, hollow floors or furniture. Suitable for installation into concrete during the casting process. With inlets for other types of conductors/cables or conduits. With rigid/flexible spouts (hub), with cable retention. With clamping means for flexible conduit. Alternative design with fire protecting pad. Minimum and maximum temperature during installation -25°C to +60°C. Maximum temperature during the casting process +90°C. Class Ha. IP30

Signature

Jiyea Gim

Jiyea Gim

Certification department

Date of Issue 2026-08-24

Working for a more sustainable future
Please do not print

Nemko Group AS
Philip Pedersens vei 11
1366 Lysaker, Norway
TEL +47 22 96 03 30
info@nemko.com
ENTERPRISE NUMBER
NO974404532

www.nemko.com

CERTIFICATE

P26229023/A1

Product	Concrete and hollow wall boxes
Variant	4
Model/Type Ref.	RED15MBB-13
Ratings.	-
Brandname / Trademark (if different from page 1)	
Principal Characteristics	1.5M big box low model 13mm of insulated material supplied with screws. Flush, semi-flush or embedded in hollow walls, hollow ceilings, hollow floors or furniture. Suitable for installation into concrete during the casting process. With inlets for other types of conductors/cables or conduits. With rigid/flexible spouts (hub), with cable retention. With clamping means for flexible conduit. Alternative design with fire protecting pad. Minimum and maximum temperature during installation -25°C to +60°C. Maximum temperature during the casting process +90°C. Class Ha. IP30

Product	Concrete and hollow wall boxes
Variant	5
Model/Type Ref.	RED15MBB-26
Ratings.	-
Brandname / Trademark (if different from page 1)	
Principal Characteristics	1.5M big box low model 26mm of insulated material supplied with screws. Flush, semi-flush or embedded in hollow walls, hollow ceilings, hollow floors or furniture. Suitable for installation into concrete during the casting process. With inlets for other types of conductors/cables or conduits. With rigid/flexible spouts (hub), with cable retention. With clamping means for flexible conduit. Alternative design with fire protecting pad. Minimum and maximum temperature during installation -25°C to +60°C. Maximum temperature during the casting process +90°C. Class Ha. IP30

Product	Concrete and hollow wall boxes
Variant	6
Model/Type Ref.	RED1MBB
Ratings.	-
Brandname / Trademark (if different from page 1)	
Principal Characteristics	1M big box low model 13mm of insulated material supplied with screws. Flush, semi-flush or embedded in hollow walls, hollow ceilings, hollow floors or furniture. Suitable for installation into concrete during the casting process. With inlets for other types of conductors/cables or conduits. With rigid/flexible spouts (hub), with cable retention. With clamping means for flexible conduit. Alternative design with fire protecting pad. Minimum and maximum temperature during installation -25°C to +60°C. Maximum temperature during the casting process +90°C. Class Ha. IP30

Signature

Jiyea Gim

Jiyea Gim

Certification department

Date of Issue 2026-08-24

Working for a more sustainable future
Please do not print

Nemko Group AS
Philip Pedersens vei 11
1366 Lysaker, Norway
TEL +47 22 96 03 30
info@nemko.com
ENTERPRISE NUMBER
NO974404532

www.nemko.com

CERTIFICATE

P26229023/A1

Product	Concrete and hollow wall boxes
Variant	7
Model/Type Ref.	RED15M-13/26
Ratings.	-
Brandname / Trademark (if different from page 1)	
Principal Characteristics	1.5M box low model 13/26mm of insulated material supplied with screws. Flush, semi-flush or embedded in hollow walls, hollow ceilings, hollow floors or furniture. Suitable for installation into concrete during the casting process. With inlets for other types of conductors/cables or conduits. With rigid/flexible spouts (hub), with cable retention. With clamping means for flexible conduit. Alternative design with fire protecting pad. Minimum and maximum temperature during installation -25°C to +60°C. Maximum temperature during the casting process +90°C. Class Ha. IP30

Nemko Group AS
Philip Pedersens vei 11
1366 Lysaker, Norway
TEL +47 22 96 03 30
info@nemko.com
ENTERPRISE NUMBER
NO974404532

Signature

Jiyea Gim

Jiyea Gim

Certification department

Date of Issue

2026-08-24

Working for a more sustainable future
Please do not print

www.nemko.com