




Data Sheet 4541136

Product: Plus WL bryter 4k dim I PH
EI-number: 4541136
Mat.no: EKO04248
EAN: 7020160424815
Packing: 1
Color: Polarwhite



Product description: ELKO Wireless switch 4ch dim is a combiunit with switch and dimmer integrated. Max load on the dimmer is 250W ohmic load. The integrated dimmer is controlled by two of the buttons on the switch or via other WL switches in the system. The combiunit has 4 pushbuttons and can control relays, dimmers or activate different scenarios in addition to control the integrated dimmer. It can be mounted in regular flush mounted boxes or in surface housings.

Technical specifications: Radiofrequency: 868MHz, GFSK-modulation, data rate 2,4 kbps.
Range: 300 m outdoors, 10-50 m indoors.

SWITCH :

Battery type: CR2032 (included).
Battery lifetime: 5-10 years or 40 000 operations.
Degree of protection: IP20.

DIMMER:

Degree of protection: IP20.
Max load:
20-250VA lightbulbs, electronic or iron trafos.
Overloadprotection
Electronic temperaturefuse and shortcircuit fuse with auto reset.
Thermofuse release at 115°C - no reset.
Screwless termination for 2x 2,5 mm² cable
Color: Polarwhite


ELKO AS

E-mail: elko@elko.no
Internet: www.elko.no
Bank: 6219.05.15880
Org.no.: NO 911 382 563 MVA


ELKO Front office
Sandstuveien 68, NO-0680 Oslo
P.O.Box 6598 Etterstad, NO-0607 Oslo
Tel.: +47 67 80 73 00
Fax: +47 67 80 73 01

ELKO Plant
Sporpind Industriområde, NO-3340 Åmot
Tel.: +47 32 78 91 00
Fax: +47 32 78 91 01

Size



Wiring diagram



ELKO AS

E-mail: elko@elko.no
Internet: www.elko.no
Bank: 6219.05.15880
Org.no.: NO 911 382 563 MVA

ELKO Front office
Sandstuveien 68, NO-0680 Oslo
P.O.Box 6598 Etterstad, NO-0607 Oslo
Tel.: +47 67 80 73 00
Fax: +47 67 80 73 01

ELKO Plant
Sporpind Industriområde, NO-3340 Åmot
Tel.: +47 32 78 91 00
Fax: +47 32 78 91 01